

Safety Data Sheet



1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: 122-89812 DULUX PREPLOCK SHELLAC STAIN BLOCKER

Recommended Use: Surface coating. Applied by brush, roller or spray.

Supplier: Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd
ABN: 67 000 049 427
Street Address: 1956 Dandenong Road,
Clayton, Victoria
Australia
Telephone Number: +61 3 9263 5678
Facsimile: +61 3 9263 5777
Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

Poisons Schedule: None allocated.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS Number | Proportion | Risk Phrases |
|--|------------|------------|---------------|
| Pigments | - | 30-60% | - |
| Ethyl alcohol | 64-17-5 | 30-60% | R11 |
| Resin | - | 10-<30% | - |
| Isopropyl alcohol | 67-63-0 | 1-<10% | R11, R36, R67 |
| Ingredients determined not to be hazardous | - | to 100% | - |

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

Product Name: 122-89812 DULUX PREPLOCK SHELLAC
STAIN BLOCKER
Substance No: 000000021220

Issued: 24/05/2010

Version: 4

Safety Data Sheet

**Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

Medical attention and special treatment:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazards from combustion products:

Highly flammable liquid. On burning will emit toxic fumes, including those of oxides of carbon .

Precautions for fire fighters and special protective equipment:

Keep containers cool with water spray. If safe to do so, remove containers from path of fire. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media:

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

Hazchem Code: · 3YE

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

Methods and materials for containment and clean up:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Conditions for safe storage:

Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits: No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Product Name: 122-89812 DULUX PREPLOCK SHELLAC

STAIN BLOCKER

Substance No: 000000021220

Issued: 24/05/2010

Version: 4

Safety Data Sheet



Ethyl alcohol: 8hr TWA = 1880 mg/m³ (1000 ppm)

Isopropyl alcohol: 8hr TWA = 983 mg/m³ (400 ppm), 15 min STEL = 1230 mg/m³ (500 ppm)

As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: G - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: Avoid contact with eyes and skin. Use with adequate ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Physical state: | Viscous liquid |
| Odour: | Solvent |
| Solubility: | Soluble in organic solvents. Insoluble in water. |
| Specific Gravity: | 1.26 |
| Relative Vapour Density (air=1): | >1 |
| Vapour Pressure (20 °C): | Not available |
| Flash Point (°C): | 13 (Ethanol) |
| Flammability Limits (%): | Not available |

Product Name: 122-89812 DULUX PREPLOCK SHELLAC
STAIN BLOCKER
Substance No: 000000021220

Issued: 24/05/2010

Version: 4



9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------------------------|----------------|
| Autoignition Temperature (°C): | Not available |
| % Volatile by Weight: | Not available |
| Solubility in water (g/L): | Negligible |
| Melting Point/Range (°C): | Not applicable |
| Boiling Point/Range (°C): | Not available |
| Decomposition Point (°C): | Not available |
| pH: | Not applicable |
| Viscosity: | Not available |
| Evaporation Rate: | Not available |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Chemical stability: | Stable under normal conditions of use. |
| Conditions to avoid: | Avoid exposure to heat, sources of ignition, and open flame. |
| Incompatible materials: | Incompatible with oxidising agents. |
| Hazardous decomposition products: | Oxides of carbon. |
| Hazardous reactions: | Hazardous polymerisation will not occur. |

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

| | |
|----------------------|--|
| Ingestion: | Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. |
| Eye contact: | May be an eye irritant. |
| Skin contact: | Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. |
| Inhalation: | Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. |

Long Term Effects:
No information available for the product.

Toxicological Data: No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Product Name: 122-89812 DULUX PREPLOCK SHELLAC
STAIN BLOCKER
Substance No: 000000021220

Issued: 24/05/2010

Version: 4



13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Advise flammable nature. Normally suitable for incineration by an approved agent.

14. TRANSPORT INFORMATION

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No: 1263
Class-primary 3 Flammable Liquid
Packing Group: II
Proper Shipping Name: PAINT
Hazchem Code: . 3YE

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No: 1263
Class-primary: 3 Flammable Liquid
Packing Group: II
Proper Shipping Name: PAINT

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No: 1263
Class-primary: 3 Flammable Liquid
Packing Group: II
Proper Shipping Name: PAINT

15. REGULATORY INFORMATION

Classification: Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Product Name: 122-89812 DULUX PREPLOCK SHELLAC
STAIN BLOCKER
Substance No: 000000021220

Issued: 24/05/2010

Version: 4



16. OTHER INFORMATION

Reason(s) for Issue:

Revised Primary SDS

This safety data sheet has been prepared by SH&E Shared Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.