

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** 514-84195 DULUX PROFESSIONAL STAIN BLOCKER

**Recommended Use:** Solvent based surface coating. Applied by brush.

**Supplier:** Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd  
**ABN:** 67 000 049 427  
**Street Address:** 1956 Dandenong Road,  
Clayton, Victoria  
Australia  
**Telephone Number:** +61 3 9263 5678  
**Facsimile:** +61 3 9263 5777  
**Emergency Telephone:** 1 800 033 111 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

**Poisons Schedule:** None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Ethyl alcohol	64-17-5	30-60%	R11
Resin	-	10-<30%	-
Pigments	-	30-60%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

### Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

### Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Product Name: 514-84195 DULUX PROFESSIONAL STAIN  
BLOCKER  
Substance No: 000013667406

Issued: 09/01/2006

Version: 3

# Safety Data Sheet

**Ingestion:**

If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

**Medical attention and special treatment:**

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazards from combustion products:**

Highly flammable liquid. On burning will emit toxic fumes, including those of oxides of carbon .

**Precautions for fire fighters and special protective equipment:**

Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Suitable Extinguishing Media:**

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

**Hazchem Code:** · 3YE

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures:**

If contamination of sewers or waterways has occurred advise local emergency services.

**Methods and materials for containment and clean up:**

**SMALL SPILLS:** Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

**LARGE SPILLS:** Shut off all possible sources of ignition. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

**Conditions for safe storage:**

Store in a well ventilated area away from foodstuffs, oxidising agents and sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

**Precautions for safe handling:**

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed. Vapour may travel a considerable distance to source of ignition and flash back.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

# Safety Data Sheet



Ethyl alcohol: 8hr TWA = 1880 mg/m<sup>3</sup> (1000 ppm)

As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Engineering controls:

Use in well ventilated areas. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

## Personal Protective Equipment:

Personal Protection: NOT IN USE

Always wash hands before smoking, eating, drinking or using the toilet. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous liquid
Colour:	Coloured
Odour:	Solvent
Solubility:	Insoluble in water. Soluble in organic solvents.
Specific Gravity:	1.25 @20°C
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	13 (Ethyl alcohol)
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	N Av
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	N Av
Decomposition Point (°C):	N Av
pH:	N App
Viscosity:	N Av
Evaporation Rate:	N Av



## 10. STABILITY AND REACTIVITY

<b>Chemical stability:</b>	Stable under normal conditions of use.
<b>Conditions to avoid:</b>	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame.
<b>Incompatible materials:</b>	Incompatible with oxidising agents.
<b>Hazardous decomposition products:</b>	Oxides of carbon.
<b>Hazardous reactions:</b>	None known.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

<b>Ingestion:</b>	Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
<b>Eye contact:</b>	May be an eye irritant.
<b>Skin contact:</b>	Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.
<b>Inhalation:</b>	Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

### Long Term Effects:

No information available for the product.

**Toxicological Data:** No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains. Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved. For ETHANOL (ETHYL ALCOHOL) (1):

Oral LD50 (rat): 7060 mg/kg

Inhalation LC50 (rat): 20,000 ppm/10 hr

SKIN: Mild irritant (rabbit).

A study of the effects of ethanol inhalation in humans found that at between 5000-10000 ppm subjects experienced coughing and smarting of the eyes and nose, with symptoms disappearing within minutes. People exposed at 15000 ppm experienced continuous lacrimation and coughing. Irritation of the eyes and respiratory tract were not noted at concentrations below 5000 ppm. Repeated or prolonged exposure to relatively high doses of ethanol may result in damage to the liver leading to cirrhosis.

There is no clear evidence that ethanol is carcinogenic in laboratory animals; it is however a tumour promoter. Ethanol is typically inactive in genotoxic assays, but on some occasions a weak response has been noted. Oral exposure to ethanol produces malformations and developmental toxicity in rats and mice at maternally toxic doses. No developmental effects were observed in rats from inhalation at doses up to 20,000 ppm.

Product Name: 514-84195 DULUX PROFESSIONAL STAIN  
BLOCKER

Substance No: 000013667406

Issued: 09/01/2006

Version: 3



## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

For large quantities: Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent. For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary** 3 Flammable Liquid  
**Packing Group:** II  
**Proper Shipping Name:** PAINT  
**Hazchem Code:** - 3YE

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** II  
**Proper Shipping Name:** PAINT

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** II  
**Proper Shipping Name:** PAINT

## 15. REGULATORY INFORMATION

**Classification:** Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

**Poisons Schedule:** None allocated.

Product Name: 514-84195 DULUX PROFESSIONAL STAIN  
BLOCKER

Substance No: 000013667406

Issued: 09/01/2006

Version: 3

# Safety Data Sheet



All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

(1) Material Safety Data Sheet - Australia Pty Ltd;  
05/ 2004.

**Reason(s) for Issue:**

Revised Primary SDS  
Format change

This safety data sheet has been prepared by SH&E Shared Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.