



# Safety Data Sheet

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT

**Recommended Use:** Wood finish.

**Supplier:** Orica Woodcare New Zealand

**Street Address:** 150 Hutt Park Road  
Lower Hutt, New Zealand

**Telephone Number:** +64 4 576 6400

**Facsimile:** + 64 4 576 6496

**Emergency Telephone:** 0 800 734 607 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

Classified as a Dangerous Good according to NZS 5433:1999 Transport of Dangerous Goods on Land.

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

**Subclasses:** Subclass 3.1 Category C (medium hazard) - Flammable Liquids.  
Subclass 6.1 Category D - Substances which are acutely toxic.  
Subclass 6.3 Category B - Substances that are mildly irritating to the skin.  
Subclass 6.4 Category A - Substances that are irritating to the eye.  
Subclass 6.5 Category A - Substances that are respiratory sensitisers.  
Subclass 6.5 Category B - Substances that are contact sensitisers.  
Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Surface Coatings and Colourants (Flammable) Group Standard 2006

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components / CAS Number	Proportion	Risk Phrases
Solvent naphtha (petroleum), light arom. 64742-95-6	30-60%	R65
Isocyanate prepolymer -	10-<30%	-
1-methoxy-2-propyl propionate 148462-57-1	10-<30%	-
Propylene glycol monomethyl ether acetate 108-65-6	1-<10%	R10, R36
Hexamethylene diisocyanate 822-06-0	<0.15%	R23 R36/37/38 R42/43

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT

**Substance No:** 000000010819

**Issued:** 23/06/2006

**Version:** 2



# Safety Data Sheet

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

**Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discoloration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

**Skin Contact:** If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

**Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:** Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek immediate medical assistance.

**Medical attention and special treatment:** Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

**Hazards from combustion products:** Flammable liquid. On burning will emit toxic fumes, including those of oxides of carbon and oxides of nitrogen .

**Precautions for fire fighters and special protective equipment:** Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

**Suitable Extinguishing Media:** Normal foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem Code:** 3Y

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures:** If contamination of sewers or waterways has occurred advise local emergency services.

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT  
**Substance No:** 000000010819

**Issued:** 23/06/2006

**Version:** 2



# Safety Data Sheet

**Methods and materials for containment and clean up:** Shut off all possible sources of ignition. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Avoid skin and eye contact and breathing in vapour. May form flammable vapour mixtures with air. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

**Conditions for safe storage:** Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits:

No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

Isocyanates, all, (as -NCO): WES-TWA 0.02 mg/m<sup>3</sup>; WES-STEL 0.07 mg/m<sup>3</sup>, sen

As published by the New Zealand Occupational Safety and Health Service (OSH).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

WES - STEL (Workplace Exposure Standard - Short Term Exposure Limits) - The 15 minute average exposure standard. Applies to any 15 minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both short-term and eight-hour, time-weighted average exposures should be determined.

'Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT  
**Substance No:** 000000010819

**Issued:** 23/06/2006 **Version:** 2



# Safety Data Sheet

## Engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

## Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Orica Personal Protection Guide No. 1, 1998: G - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Viscous liquid
<b>Colour:</b>	Pale Yellow
<b>Odour:</b>	Solvent
<b>Solubility:</b>	Insoluble in water. Soluble in organic solvents.
<b>Specific Gravity:</b>	0.985 @20°C
<b>Relative Vapour Density (air=1):</b>	>1
<b>Vapour Pressure (20 °C):</b>	N Av
<b>Flash Point (°C):</b>	45°C
<b>Flammability Limits (%):</b>	0.8-6
<b>Autoignition Temperature (°C):</b>	N Av
<b>% Volatile by Weight:</b>	N Av
<b>Solubility in water (g/L):</b>	Insoluble
<b>Melting Point/Range (°C):</b>	N App
<b>Boiling Point/Range (°C):</b>	155-174
<b>pH:</b>	N App
<b>Viscosity:</b>	N Av
<b>Evaporation Rate:</b>	N Av

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions of use.

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT  
**Substance No:** 000000010819

**Issued:** 23/06/2006

**Version:** 2



# Safety Data Sheet

- Conditions to avoid:** Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame. Avoid exposure to moisture.
- Incompatible materials:** Incompatible with oxidising agents.
- Hazardous decomposition products:** Isocyanates. Oxides of carbon. Oxides of nitrogen.
- Hazardous reactions:** Reacts with moisture liberating carbon dioxide.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

- Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
- Eye contact:** May be an eye irritant.
- Skin contact:** Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis. Component/s of this material can be absorbed through the skin with resultant adverse effects.
- Inhalation:** Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. May cause respiratory sensitisation in sensitive individuals, producing asthma-like symptoms.

### Long Term Effects:

No information available for the product. For the major solvent (1) : Evidence indicates that repeated or prolonged exposure to this chemical could result in central nervous system disorders.

### Toxicological Data:

No LD50 data available for the product. The toxicity of the product may be attributed to the solvents it contains. Additive effects may occur with mixtures of solvents. Similar effects can occur where the consumption of alcohol is also involved. However, for constituent(s) Solvent naphtha (petroleum), light arom. (1):

- Oral LD50 (rat): >2000 mg/kg  
Dermal LD50 (rabbit): >2000 mg/kg  
Inhalation LC50 (rat): 1320 ppm/6 Hrs/90 days

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT  
**Substance No:** 000000010819

**Issued:** 23/06/2006 **Version:** 2



# Safety Data Sheet

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

**Disposal methods:** Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as a Dangerous Good according to NZS 5433:1999 Transport of Dangerous Goods on Land.

**UN No:** 1263  
**Class-primary** 3 Flammable Liquid  
**Packing Group:** III  
**Proper Shipping Name:** PAINT  
**Hazchem Code:** 3Y

### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 1263  
**Class-primary:** 3 Flammable Liquid  
**Packing Group:** III  
**Proper Shipping Name:** PAINT

## 15. REGULATORY INFORMATION

**Classification:** Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT  
**Substance No:** 000000010819

**Issued:** 23/06/2006 **Version:** 2



# Safety Data Sheet

2001.

**Subclasses:** Subclass 3.1 Category C (medium hazard) - Flammable Liquids.  
Subclass 6.1 Category D - Substances which are acutely toxic.  
Subclass 6.3 Category B - Substances that are mildly irritating to the skin.  
Subclass 6.4 Category A - Substances that are irritating to the eye.  
Subclass 6.5 Category A - Substances that are respiratory sensitisers.  
Subclass 6.5 Category B - Substances that are contact sensitisers.  
Subclass 9.1 Category B - Substances that are ecotoxic in the aquatic environment.

Surface Coatings and Colourants (Flammable) Group Standard 2006

## 16. OTHER INFORMATION

(1) Supplier Material Safety Data Sheet; 12/ 2003.

This material safety data sheet has been prepared by SH&E Shared Services, Orica.

### Reason(s) for Issue:

Format change  
Change in Formulation  
Alignment to HSNO requirements

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

**Product Name:** 552-97145 INTERGRAIN MAXIPROOF MATT  
**Substance No:** 00000010819

**Issued:** 23/06/2006

**Version:** 2