

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** 539-82010 CABOTS CABOTHANE CLEAR WATER BASED GLOSS

**Recommended Use:** Surface coating. Applied by brush, roller or spray.

**Supplier:** Cabot's New Zealand, a division of DuluxGroup (New Zealand) Pty Ltd  
ABN 55 133 404 118  
Co. 2355191

**Street Address:** 150 Hutt Park Road  
Lower Hutt, New Zealand

**Telephone Number:** +64 4 576 6400

**Facsimile:** + 64 4 576 6496

**Emergency Telephone:** 0 800 734 607 (ALL HOURS)

## 2. HAZARDS IDENTIFICATION

Not classified as a Dangerous Good under NZS 5433:2007 Transport of Dangerous Goods on Land.

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Water	7732-18-5	>60%	-
Synthetic polymer(s)	-	10-<30%	-
Propylene glycol	57-55-6	<1%	-
Ingredients determined not to be hazardous	-	to 100%	-

## 4. FIRST AID MEASURES

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

### Skin Contact:

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

### Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

### Ingestion:

Rinse mouth with water. If swallowed, give a glass of water to drink. Seek medical advice.

### Medical attention and special treatment:

Treat symptomatically.

Product Name: 539-82010 CABOTS CABOTHANE CLEAR  
WATER BASED GLOSS  
Substance No: 000014290701

Issued: 19/07/2011

Version: 6

## 5. FIRE FIGHTING MEASURES

### Hazards from combustion products:

Not combustible, however following evaporation of the water component of the material, the residual material can burn if ignited. On burning will emit toxic fumes, including those of oxides of carbon and oxides of nitrogen .

### Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

### Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

### Methods and materials for containment and clean up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Keep out of reach of children. Avoid eye contact and repeated or prolonged skin contact.

**Conditions for safe storage:** Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the New Zealand Occupational Safety and Health Service (OSH). However, Workplace Exposure Standard(s) for constituent(s):

Propane-1,2-diol (propylene glycol) (vapour & particulates): WES-TWA 150 ppm, 474 mg/m<sup>3</sup>; (particulates only): WES-TWA 10 mg/m<sup>3</sup>.

# Safety Data Sheet



As published by the New Zealand Occupational Safety and Health Service (OSH).

WES - TWA (Workplace Exposure Standard - Time Weighted Average) - The eight-hour, time-weighted average exposure standard is designed to protect the worker from the effects of long-term exposure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

## Personal Protective Equipment:

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: B - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.



MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: No special personal protective equipment required. If there is a risk of eye contact and repeated or prolonged skin contact wear gloves and safety glasses. Wash hands after use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Viscous liquid
<b>Odour:</b>	Bland
<b>Solubility:</b>	Miscible with water.
<b>Specific Gravity:</b>	1.03 @20°C
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	Not applicable
<b>Flammability Limits (%):</b>	Not applicable
<b>Autoignition Temperature (°C):</b>	Not applicable
<b>% Volatile by Weight:</b>	Not available
<b>Solubility in water (g/L):</b>	Miscible
<b>Melting Point/Range (°C):</b>	Not applicable
<b>Boiling Point/Range (°C):</b>	100 (water)
<b>Decomposition Point (°C):</b>	Not available
<b>pH:</b>	8-9
<b>Viscosity:</b>	Not available

Product Name: 539-82010 CABOTS CABOTHANE CLEAR  
WATER BASED GLOSS  
Substance No: 000014290701

Issued: 19/07/2011

Version: 6

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Evaporation Rate:** Not available

## 10. STABILITY AND REACTIVITY

**Chemical stability:** Stable under normal conditions of use.

**Conditions to avoid:** Avoid contact with foodstuffs. Avoid exposure to frost.

**Incompatible materials:** Incompatible with oxidising agents.

**Hazardous decomposition products:** Oxides of carbon. Oxides of nitrogen.

**Hazardous reactions:** Hazardous polymerisation will not occur.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

**Ingestion:** No adverse effects expected, however, large amounts may cause nausea and vomiting.

**Eye contact:** May be an eye irritant.

**Skin contact:** Contact with skin may result in irritation.

**Inhalation:** Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes of the respiratory tract, headache and nausea.

**Long Term Effects:**  
No information available for the product.

**Toxicological Data:** No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.

## 13. DISPOSAL CONSIDERATIONS

**Disposal methods:**  
For large quantities: Refer to Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for disposal at approved land waste site.  
For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Not classified as a Dangerous Good under NZS 5433:2007 Transport of Dangerous Goods on Land.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

### Classification:

Based on available information, not classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001.

## 16. OTHER INFORMATION

### Reason(s) for Issue:

Product name change

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.