

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **FB400**

Recommended Use of the Chemical and Restrictions on Use Cable bolt grout.

Supplier: Orica Australia Pty Ltd trading as Minova Australia
ABN: 99 004 117 828
Street Address: George Booth Drive,
Kurri Kurri, NSW 2327
Australia

Telephone Number: 1300 MINOVA (1300 646 682)
Facsimile: 1300 FAXMINOVA (1300 329 646)
Website: www.minovaglobal.com

Emergency Telephone: **1800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Irritation - Category 2
Skin Sensitisation - Category 1
Eye Damage - Category 1
Carcinogenicity - Category 1A
Specific target organ toxicity (single exposure) - Category 3
Specific target organ toxicity (repeated exposure) - Category 2

SIGNAL WORD: DANGER



Hazard Statement(s):

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet



Precautionary Statement(s):

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, eye and face protection.
P281 Use personal protective equipment as required.

Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Portland Cement	65997-15-1	>60%	H315 H317 H318 H335
Sand (Crystalline silica)	-	1-<10%	H350 H335 H372
Calcium hydroxide	1305-62-0	1-<5%	H315 H318 H335
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

Product Name: FB400
Substance No: 000000052086

Issued: 03/07/2017
Version: 2

Safety Data Sheet



Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre. Continue to wash with large amounts of water until medical help is available.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Media applicable to surrounding fire.

Specific hazards arising from the chemical:

Non-combustible material.

Special protective equipment and precautions for fire-fighters:

Non-combustible material.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in dust.

Conditions for safe storage, including any incompatibilities:

Store under cover in a dry place. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Calcium hydroxide: 8hr TWA = 5 mg/m³

Portland cement: 8hr TWA = 10 mg/m³

Silica Crystalline - Quartz (respirable dust): 8hr TWA = 0.1 mg/m³

Safety Data Sheet



As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Avoid generating and breathing in dusts. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, DUST MASK.



Wear overalls, chemical goggles and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Powder
Colour:	Grey
Odour:	Cementitious
Solubility:	Slightly soluble in water.
Specific Gravity:	1.2-1.6 (bulk density)
Relative Vapour Density (air=1):	Not applicable
Vapour Pressure (20 °C):	Not applicable
Flash Point (°C):	Not applicable
Flammability Limits (%):	Not applicable
Autoignition Temperature (°C):	Not applicable
% Volatile by Weight:	Not available
Melting Point/Range (°C):	Not available

Product Name: FB400
Substance No: 000000052086

Issued: 03/07/2017
Version: 2

Safety Data Sheet



Decomposition Point (°C):	Not available
pH:	11-12
Viscosity:	Not applicable
Evaporation Rate:	Not applicable

10. STABILITY AND REACTIVITY

Reactivity:	Reacts with acids.
Chemical stability:	Stable under normal conditions of use.
Possibility of hazardous reactions:	None known.
Conditions to avoid:	Avoid exposure to moisture. Avoid dust generation.
Incompatible materials:	Incompatible with acids, oxidising agents, ethanol and interhalogens.
Hazardous decomposition products:	Not known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing may result in irritation of the gastrointestinal tract.
Eye contact:	A severe eye irritant. Contamination of eyes can result in permanent injury.
Skin contact:	Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
Inhalation:	Material is irritant to the mucous membranes of the respiratory tract (airways).
Acute toxicity:	No LD50 data available for the product.
Skin corrosion/irritation:	Irritant.
Serious eye damage/irritation:	Causes serious eye damage.
Respiratory or skin sensitisation:	A skin sensitiser.

Chronic effects: Repeated or prolonged breathing of silica dust may lead to pulmonary disorders including silicosis and cancer.

Mutagenicity:	Not classified.
Carcinogenicity:	May cause cancer. For Crystalline silica: This material has been classified by the International Agency for Research on Cancer (IARC) as a Group 1 agent. Group 1 - The agent is carcinogenic to humans.
Reproductive toxicity:	Not classified.
Specific Target Organ Toxicity (STOT) - single exposure:	May cause respiratory irritation.
Specific Target Organ Toxicity (STOT) - repeated exposure:	May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet



Aspiration hazard: Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Irritation - Category 2

Skin Sensitisation - Category 1

Eye Damage - Category 1

Carcinogenicity - Category 1A

Specific target organ toxicity (single exposure) - Category 3

Specific target organ toxicity (repeated exposure) - Category 2

Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Poisons Schedule (SUSMP): None allocated.

16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Product Name: FB400
Substance No: 000000052086

Issued: 03/07/2017
Version: 2

Safety Data Sheet

**Reason(s) for Issue:**

Revised Primary SDS
Change in company details
Change in Hazardous Chemical Classification
Update in Toxicological Information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since The Supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Supplier representative or The Supplier at the contact details on page 1.

The Supplier's responsibility for the material as shipped is subject to the terms and conditions of sale, a copy of which is available upon request.