

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FOAMED CEMENTS

Other name(s): Air-O-Cem; Tekseal; Tekseal S; Tekseal HD; Tekseal HS / HS Fast

Recommended Use of the Chemical Ventilation seals and cavity filling.

and Restrictions on Use

Supplier: Orica Australia Pty Ltd trading as Minova Australia

ABN: 99 004 117 828
Street Address: George Booth Drive,
Kurri Kurri, NSW 2327

Australia

 Telephone Number:
 1300 MINOVA (1300 646 682)

 Facsimile:
 1300 FAXMINOVA (1300 329 646)

 Emergency Telephone:
 1800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia: HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Irritation - Category 2 Skin Sensitisation - Category 1B Eye Damage - Category 1

Specific target organ toxicity (single exposure) - Category 3

SIGNAL WORD: DANGER





Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Precautionary Statement(s):

Prevention:

P104 Read Safety Data Sheet before use.

P261 Avoid breathing dust.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye and face protection.

Product Name: FOAMED CEMENTS
Substance No: 000000052129

Version: 4

Issued: 29/06/2017



Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): None allocated.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Hazard Codes
Portland Cement	65997-15-1	10-<50%	H315 H317 H318 H335
Calcium sulfate	7778-18-9	10-<30%	-
Slags, ferrous metal, blast furnace	65996-69-2	10-<30%	H315 H319 H335
Calcium hydroxide	1305-62-0	<2.5%	H315 H318 H335
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

Immediately wash in and around the eye area with large amounts of water for at least 15 minutes. Eyelids to be held apart. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport promptly to hospital or medical centre. Continue to wash with large amounts of water until medical help is available.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Can cause corneal burns.

Product Name: FOAMED CEMENTS

Issued: 29/06/2017 Substance No: 000000052129 Version: 4



5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Not combustible, however, if material is involved in a fire use: Extinguishing media appropriate to surrounding fire conditions.

Specific hazards arising from the chemical:

Non-combustible material.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Clear area of all unprotected personnel. Avoid breathing in dust. Work up wind or increase ventilation. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact and breathing in dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid skin and eye contact and breathing in dust.

Conditions for safe storage, including any incompatibilities:

Store under cover in a dry place. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for spills.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Portland cement: 8hr TWA = 10 mg/m³ Calcium sulfate: 8hr TWA = 10 mg/m³ Calcium hydroxide: 8hr TWA = 5 mg/m³

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Product Name: FOAMED CEMENTS Issued: 29/06/2017 Substance No: 000000052129



Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Avoid generating and breathing in dusts. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, DUST MASK.









Wear overalls, chemical goggles and impervious gloves. Avoid generating and inhaling dusts. If determined by a risk assessment an inhalation risk exists, wear a dust mask/respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Powder

Colour: Grey / Light Brown None to Cementitious Odour:

Odour Threshold: Not available Insoluble in water. Solubility: **Specific Gravity:** 1.2 - 1.5 (bulk density)

Relative Vapour Density (air=1): Not applicable Not applicable Vapour Pressure (20 °C): Flash Point (°C): Not applicable Not applicable Flammability Limits (%): **Autoignition Temperature (°C):** Not applicable % Volatile by Weight: Not available Melting Point/Range (°C): Not available **Decomposition Point (°C):** Not available pH: 11.2 - 12**Viscosity:** Not applicable **Evaporation Rate:** Not applicable

10. STABILITY AND REACTIVITY

Reactivity: Reacts with acids.

Chemical stability: Stable under normal conditions of use.

Product Name: FOAMED CEMENTS Issued: 29/06/2017 Substance No: 000000052129



Possibility of hazardous

reactions:

Hazardous polymerisation will not occur.

Conditions to avoid: Avoid exposure to moisture.

Incompatible with acids. Incompatible materials:

Hazardous decomposition

products:

Not known.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Swallowing may result in irritation of the gastrointestinal tract. Ingestion:

A severe eye irritant. Contamination of eyes can result in permanent injury. **Eve contact:**

Skin contact: Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged

skin contact may lead to allergic contact dermatitis.

Material is irritant to the mucous membranes of the respiratory tract (airways). Inhalation:

Acute toxicity: No LD50 data available for the product.

Skin corrosion/irritation: Irritant.

Serious eve damage/irritation: Causes serious eve damage.

Respiratory or skin

A skin sensitiser.

sensitisation:

Chronic effects: No information available for the product.

Specific Target Organ Toxicity May cause respiratory irritation.

(STOT) - single exposure:

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Persistence/degradability: Not readily biodegradable.

Bioaccumulative potential: No information available.

Mobility in soil: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Product Name: FOAMED CEMENTS Issued: 29/06/2017 Substance No: 000000052129



Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Irritation - Category 2 Skin Sensitisation - Category 1B Eve Damage - Category 1 Specific target organ toxicity (single exposure) - Category 3

Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Poisons Schedule (SUSMP): None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

Revised Primary SDS Change in company details Minor Text Changes

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since The Supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Supplier representative or The Supplier at the contact details on page 1.

The Supplier's responsibility for the material as shipped is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: FOAMED CEMENTS Issued: 29/06/2017 Substance No: 000000052129