

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: **LOKSET SUPAMIX RESIN CAPSULES**

Other name(s): Lokset Resin Capsule; Too speedie; Long Tendon Support Resin (F series); J Series; STS; Lokset Advance; Lokset 26; Lokset CF

Recommended Use of the Chemical and Restrictions on Use Anchoring medium for rockbolts to provide roof support in mines and tunnels.

Supplier: Orica Australia Pty Ltd trading as Minova Australia
ABN: 99 004 117 828
Street Address: George Booth Drive,
Kurri Kurri, NSW 2327
Australia

Telephone Number: 1300 MINOVA (1300 646 682)
Facsimile: 1300 FAXMINOVA (1300 329 646)
Website: www.minovaglobal.com

Emergency Telephone: **1800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; **NON-DANGEROUS GOODS.**

This material is hazardous according to Safe Work Australia; **HAZARDOUS CHEMICAL.**

Classification of the chemical:

Skin Irritation - Category 2
Eye Irritation - Category 2A
Toxic to Reproduction - Category 2
Specific target organ toxicity (repeated exposure) - Category 1

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:
Acute Aquatic Toxicity - Category 3

SIGNAL WORD: DANGER



Hazard Statement(s):

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.
H372 Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet



Precautionary Statement(s):

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist, vapours, spray.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye and face protection.
P281 Use personal protective equipment as required.

Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P321 Specific treatment (see First Aid Measures on Safety Data Sheet).
P362 Take off contaminated clothing and wash before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): S5 Caution.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Product Description: Resin mastic, inert fillers and pigment separated from white catalyst paste in a sealed plastic skin.

Components	CAS Number	Proportion	Hazard Codes
Synthetic polymer(s)	-	10-<30%	-
Styrene	100-42-5	1-<12.5%	H226 H315 H319 H332 H372 H361d
Dibenzoyl peroxide	94-36-0	<1%	H241 H319 H317
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

Product Name: LOKSET SUPAMIX RESIN CAPSULES
Substance No: 000000052018

Issued: 29/06/2017
Version: 5

Safety Data Sheet



Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the chemical:

Combustible paste. On burning will emit toxic fumes, including those of oxides of carbon.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Wear protective equipment to prevent skin and eye contact and breathing in vapours. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use non-sparking tools. Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour. Keep out of reach of children. Vapour may travel a considerable distance to source of ignition and flash back. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Flameproof equipment is necessary in all areas where this chemical is being used. Nearby equipment must be earthed.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from sources of heat or ignition. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks or spills.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Product Name: LOKSET SUPAMIX RESIN CAPSULES
Substance No: 000000052018

Issued: 29/06/2017
Version: 5

Safety Data Sheet



Benzoyl peroxide: 8hr TWA = 5 mg/m³, Sen

Styrene, monomer: 8hr TWA = 213 mg/m³ (50 ppm), 15 min STEL = 426 mg/m³ (100 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

'Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance and should not be further exposed to the substance.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Keep containers closed when not in use.

Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.



Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator or an air supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Colour:	Not available
Odour:	Slight Styrene
Solubility:	Insoluble in water.
Specific Gravity:	1.9
Relative Vapour Density (air=1):	3.6 (styrene)
Vapour Pressure (20 °C):	Not available
Flash Point (°C):	>110 (open cup)
Flammability Limits (%):	1.1 - 6.1 (styrene)
Autoignition Temperature (°C):	Not available
% Volatile by Weight:	Not available
Boiling Point/Range (°C):	Not available
Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	30,000 cPs (Brookfield RVT viscometer)
Evaporation Rate:	Not available

10. STABILITY AND REACTIVITY

Reactivity:	Reacts with oxidising agents.
Chemical stability:	Stable under normal conditions of use.
Possibility of hazardous reactions:	Hazardous polymerisation may occur if contaminated, or at elevated temperatures. Reacts with incompatible materials.
Conditions to avoid:	Avoid exposure to heat, sources of ignition, and open flame. Avoid exposure to direct sunlight.
Incompatible materials:	Incompatible with strong acids, alkalis, alkylation catalysts, copper, copper alloys, halogens, hydrogen halides, oxidising agents, peroxides and metal salts.
Hazardous decomposition products:	Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing can result in nausea, vomiting, diarrhoea, and abdominal pain.
Eye contact:	An eye irritant.
Skin contact:	Contact with skin will result in irritation.
Inhalation:	Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea.

Acute toxicity: No LD50 data available for the product. For the constituent Styrene (1):
Oral LD50 (rat): 2,650 mg/kg

Safety Data Sheet



Inhalation LC50 (rat): 11.8 mg/L/4H

Skin corrosion/irritation: Irritant.
Serious eye damage/irritation: Severe irritant.
Respiratory or skin sensitisation: Not classified.

Chronic effects:

For Styrene: Evidence indicates that repeated or prolonged exposure to this chemical by any route could result in effects on the hearing organs. This material has been classified by the International Agency for Research on Cancer (IARC) as a Group 2B. Group 2B - The agent is possibly carcinogenic to humans.

Mutagenicity: Not classified.
Carcinogenicity: Not classified.
Reproductive toxicity: Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity (STOT) - single exposure: Not classified.
Specific Target Organ Toxicity (STOT) - repeated exposure: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard: Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

Aquatic toxicity: Harmful to aquatic organisms.

48hr EC50 (Daphnia magna): For Styrene: 3.3 - 7.4 mg/L (2)
96hr LC50 (bluegill sunfish): For Styrene: 4.7 mg/L (2)

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Safety Data Sheet



Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Skin Irritation - Category 2

Eye Irritation - Category 2A

Toxic to Reproduction - Category 2

Specific target organ toxicity (repeated exposure) - Category 1

The following health/environmental hazard categories fall outside the scope of the Workplace Health and Safety Regulations:

Acute Aquatic Toxicity - Category 3

Hazard Statement(s):

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Poisons Schedule (SUSMP): S5 Caution.

16. OTHER INFORMATION

(1) 'Registry of Toxic Effects of Chemical Substances'. Ed. D. Sweet, US Dept. of Health & Human Services: Cincinnati, 2017.

(2) ECOTOX Database, U.S. Environmental Protection Agency (EPA).

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

Revised Primary SDS

Change in company details

Change in Hazardous Chemical Classification

Alignment to GHS requirements

Change in First Aid Measures

Change in Personal Protection Requirements

Update in Toxicological Information

Update in Ecological Information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since The Supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Supplier representative or The Supplier at the contact details on page 1.

The Supplier's responsibility for the material as shipped is subject to the terms and conditions of sale, a copy of which is available upon request.