

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: GEOFLEX (COMPONENT B)

Recommended Use of the Chemical Part B of a two component silicate injection resin. Mixed with Geoflex (Component A). and Restrictions on Use

Supplier: Minova Australia Pty Ltd ABN: ABN: 084 965 962 Street Address: 102 Albatross Road. Nowra, NSW 2541

Australia

Telephone Number: 1300 MINOVA (1300 646 682) Facsimile: 1300 FAXMINOVA (1300 329 646)

Website: www.minovaglobal.com

Emergency Telephone: 1800 033 111 (ALL HOURS)

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

2. HAZARDS IDENTIFICATION

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia: HAZARDOUS CHEMICAL.

Classification of the chemical:

Acute Inhalation Toxicity - Category 4 Skin Irritation - Category 2 Skin Sensitisation - Category 1 Eye Irritation - Category 2A Respiratory Sensitisation - Category 1 Carcinogenicity - Category 2 Specific target organ toxicity (single exposure) - Category 3

Specific target organ toxicity (repeated exposure) - Category 2

SIGNAL WORD: DANGER





Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Product Name: GEOFLEX (COMPONENT B)

Substance No: 000000052091

Version: 3

Issued: 06/07/2017



Precautionary Statement(s):

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe fumes, mists, vapours, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves, protective clothing, eye and face protection.

P281 Use personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.

Response:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

Poisons Schedule (SUSMP): S6 Poison.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Product Description: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

Components	CAS Number	Proportion	Hazard Codes
Isocyanic acid, polymethylene polyphenylene ester	9016-87-9	>60%	H332 H319 H335 H315
			H351 H334 H317 H373
Diphenylmethane-4,4-diisocyanate	101-68-8	25-35%	H315 H317 H319 H332
			H334 H335 H351 H373
Ingredients determined not to be hazardous	-	to 100%	-

4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

Product Name: GEOFLEX (COMPONENT B) Issued: 06/07/2017

Substance No: 00000052091 Version: 3



Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water and soap. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Indication of immediate medical attention and special treatment needed:

Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards arising from the chemical:

Combustible liquid. On burning will emit toxic fumes, including those of oxides of nitrogen, isocyanates, hydrogen cyanide and oxides of carbon.

Special protective equipment and precautions for fire-fighters:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. If safe to do so, remove containers from path of fire. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Emergency procedures/Environmental precautions:

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

7. HANDLING AND STORAGE

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S6 and must be stored, maintained and used in accordance with the relevant regulations.

Product Name: GEOFLEX (COMPONENT B) Issued: 06/07/2017

Substance No: 00000052091 Version: 3



Precautions for safe handling:

Avoid skin and eye contact and breathing in vapour, mists and aerosols.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated place and out of direct sunlight. Keep dry - reacts with water, may lead to drum rupture. Store away from incompatible materials described in Section 10. Store away from foodstuffs. Do not store below 10 degrees centigrade. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Isocyanates, all (as -NCO): 8hr TWA = 0.02 mg/m³, 15 min STEL = 0.07 mg/m³, Sen

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

STEL (Short Term Exposure Limit) - the airborne concentration of a particular substance calculated as a time-weighted average over 15 minutes, which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

`Sen' Notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance and should not be further exposed to the substance.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Appropriate engineering controls:

Ensure ventilation is adequate to maintain air concentrations below Workplace Exposure Standards. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Product Name: GEOFLEX (COMPONENT B)

Substance No: 000000052091

Version: 3

Issued: 06/07/2017











Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator or an air supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Dark Brown Colour:

Odour: Characteristic, Weak Solubility: Immiscible with water.

Specific Gravity: 1.13 @ 20°C Relative Vapour Density (air=1): Not available Vapour Pressure (20 °C): 1.105 kPa Flash Point (°C): >100

Flammability Limits (%): Not available **Autoignition Temperature (°C):** Not available % Volatile by Weight: Not available

Boiling Point/Range (°C): >200

Decomposition Point (°C): Not available :Ha Not applicable 150 mPa.s @ 25°C **Viscosity:**

Evaporation Rate: Not available

10. STABILITY AND REACTIVITY

Reactivity: Reacts with water.

Stable under normal conditions of use. Chemical stability:

Possibility of hazardous

reactions:

Reacts exothermically with water liberating carbon dioxide.

Conditions to avoid: Avoid exposure to heat, sources of ignition, and open flame. Avoid exposure to

moisture.

Incompatible with acids, alcohols, amines, water, ammonia, bases, metal Incompatible materials:

compounds and oxidising agents.

Hazardous decomposition

Substance No: 000000052091

products:

Oxides of nitrogen. Isocyanates. Hydrogen cyanide. Oxides of carbon.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Product Name: GEOFLEX (COMPONENT B) Issued: 06/07/2017

Version: 3



Swallowing can result in nausea, vomiting and central nervous system depression. Ingestion:

> If the victim is showing signs of central system depression (like those of drunkeness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs. Breathing in vomit may lead to aspiration

pneumonia (inflammation of the lung).

An eye irritant. Eye contact:

Skin contact: Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged

skin contact may lead to allergic contact dermatitis.

Inhalation: Material is irritant to the mucous membranes of the respiratory tract (airways). A

> respiratory sensitiser. Can cause possible allergic reactions, producing asthma-like symptoms. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired

judgement and if exposure is prolonged, unconsciousness.

Acute toxicity: No LD50 data available for the product. For the constituent Polymethylenepolyphenyleneisocyanate

(1):

Oral LD50 (rat): >10,000 mg/kg Dermal LD50 (rabbit): >9,400 mg/kg Inhalation LC50 (rat): 0.49 mg/L/4H

Skin corrosion/irritation: Irritant. Serious eye damage/irritation: Irritant.

Respiratory or skin A respiratory and skin sensitiser.

sensitisation:

Chronic effects: For Isocyanates: Animal studies have shown that respiratory sensitisation can be induced by skin contact with known respiratory sensitisers including diisocyanates. These results emphasise the need for protective clothing including gloves to be worn when handling these chemicals or in maintenance work.

Mutagenicity: Not classified.

Suspected of causing cancer. Carcinogenicity:

Reproductive toxicity: Not classified.

Specific Target Organ Toxicity May cause respiratory irritation.

(STOT) - single exposure:

Specific Target Organ Toxicity May cause damage to organs through prolonged or repeated exposure.

(STOT) - repeated exposure:

Aspiration hazard: Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity Avoid contaminating waterways.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

14. TRANSPORT INFORMATION

Product Name: GEOFLEX (COMPONENT B) Issued: 06/07/2017 Substance No: 000000052091

Version: 3



Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

15. REGULATORY INFORMATION

Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

Classification of the chemical:

Acute Inhalation Toxicity - Category 4
Skin Irritation - Category 2
Skin Sensitisation - Category 1
Eye Irritation - Category 2A
Respiratory Sensitisation - Category 1

Carcinogenicity - Category 2

Specific target organ toxicity (single exposure) - Category 3

Specific target organ toxicity (repeated exposure) - Category 2

Hazard Statement(s):

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Poisons Schedule (SUSMP): S6 Poison.

16. OTHER INFORMATION

(1) Supplier Safety Data Sheet; 01/2014.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

Reason(s) for Issue:

Revised Primary SDS Change in company details Minor Text Changes

Product Name: GEOFLEX (COMPONENT B) Issued: 06/07/2017

Substance No: 000000052091 Version: 3



This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since The Supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Supplier representative or The Supplier at the contact details on page 1.

The Supplier's responsibility for the material as shipped is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: GEOFLEX (COMPONENT B) Issued: 06/07/2017 Substance No: 000000052091

Version: 3