

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** **SILENT SEAL B - COMPONENT**

**Recommended Use of the Chemical and Restrictions on Use** B-component for a two component low pressure polyurethane foam system.

**Supplier:** Minova Australia Pty Ltd  
**ABN:** ABN: 084 965 962  
**Street Address:** 102 Albatross Road,  
Nowra, NSW 2541  
Australia

**Telephone Number:** 1300 MINOVA (1300 646 682)  
**Facsimile:** 1300 FAXMINOVA (1300 329 646)  
**Website:** www.minovaglobal.com

**Emergency Telephone:** **1800 033 111 (ALL HOURS)**

Please ensure you refer to the limitations of this Safety Data Sheet as set out in the "Other Information" section at the end of this Data Sheet.

## 2. HAZARDS IDENTIFICATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

### Classification of the chemical:

Gases under pressure - Compressed Gas  
Acute Oral Toxicity - Category 4  
Skin Irritation - Category 2  
Eye Irritation - Category 2A

**SIGNAL WORD:** WARNING



### Hazard Statement(s):

H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

### Precautionary Statement(s):

#### Prevention:

P202 Do not handle until all safety precautions have been read and understood.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves, protective clothing, eye and face protection.  
P285 In case of inadequate ventilation wear respiratory protection.

*Product Name:* SILENT SEAL B - COMPONENT  
*Substance No:* 000000052115

*Issued:* 15/02/2018  
*Version:* 4

# Safety Data Sheet



## Response:

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P321 Specific treatment (see First Aid Measures on Safety Data Sheet).

P362 Take off contaminated clothing and wash before reuse.

## Storage:

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

## Disposal:

P501 Dispose of contents and container in accordance with local, regional, national, international regulations.

**Poisons Schedule (SUSMP):** None allocated.

## 3. COMPOSITION AND INFORMATION ON INGREDIENTS

| Components                                 | CAS Number | Proportion | Hazard Codes   |
|--|------------|------------|----------------|
| Tris(2-chloro-1-methylethyl)phosphate      | 13674-84-5 | 20-40%     | H302 H412      |
| 1,1,1,2-Tetrafluoroethane                  | 811-97-2   | 10-20%     | H280           |
| 2,2'-Oxybis(ethanol) (Diethylene glycol)   | 111-46-6   | 5-10%      | H302           |
| Propellant (Nitrogen)                      | 7727-37-9  | <10%       | -              |
| Tertiary amine                             | 3030-47-5  | 1-5%       | H302 H311 H314 |
| Ingredients determined not to be hazardous | -          | to 100%    | -              |

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discoloration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

### Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

### Eye Contact:

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes. Use lukewarm water if possible.

### Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by the mouth to an unconscious patient. Seek medical assistance.

Product Name: SILENT SEAL B - COMPONENT

Substance No: 000000052115

Issued: 15/02/2018

Version: 4

**Indication of immediate medical attention and special treatment needed:**

Treat symptomatically. Effects may be delayed.

Epinephrine and other sympathomimetic drugs should be avoided following exposure to high propellant concentrations as cardiac arrhythmias may result with possible subsequent cardiac arrest. The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe victim for the development of cardiac arrhythmias.

## 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:**

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

**Hazchem or Emergency Action Code:** 2ZE**Specific hazards arising from the chemical:**

Combustible material. In a fire or if heated, a pressure increase will occur and the container may burst. On burning will emit toxic fumes, including those of hydrogen cyanide, hydrogen fluoride, oxides of carbon, aldehydes and oxides of nitrogen.

**Special protective equipment and precautions for fire-fighters:**

If safe to do so, remove containers from path of fire. Keep people away from and upwind of fire. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

**Emergency procedures/Environmental precautions:**

Isolate spill or leak area immediately. Clear area of all unprotected personnel. Shut off all possible sources of ignition. Work up wind or increase ventilation. Do not allow container or product to get into drains, sewers, streams or ponds. If contamination of sewers or waterways has occurred advise local emergency services.

**Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:**

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and place into approved, properly labelled open-head metal containers or drums for disposal. Wash area down with detergent and excess water.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:**

The product may be handled only by appropriately trained personnel. Read label before use. Avoid skin and eye contact and breathing in vapour, mists and aerosols. Use only in a well-ventilated area. Wear respiratory protection when handling. Do not puncture or incinerate. Contents under pressure.

**Conditions for safe storage, including any incompatibilities:**

Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store between 16°C and 32°C. Products stored below 16°C or above 32°C must be given adequate time to warm up/cool down. Protect from temperatures above 50°C. Protect from freezing. Protect containers from physical damage. Store containers in upright position. Keep containers closed when not in use - check regularly for leaks.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Safety Data Sheet



**Control Parameters:** No value assigned for this specific material by Safe Work Australia. However, Workplace Exposure Standard(s) for constituent(s):

Diethylene glycol: 8hr TWA = 100 mg/m<sup>3</sup> (23 ppm)

1,1,1,2-Tetrafluoroethane (HFC 134a): 8hr TWA = 4240 mg/m<sup>3</sup> (1000 ppm)

As published by Safe Work Australia Workplace Exposure Standards for Airborne Contaminants.

TWA - The time-weighted average airborne concentration of a particular substance when calculated over an eight-hour working day, for a five-day working week.

These Workplace Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These workplace exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## Appropriate engineering controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Use with local exhaust ventilation or while wearing organic vapour/particulate respirator.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

## Individual protection measures, such as Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.



Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If determined by a risk assessment an inhalation risk exists, wear an organic vapour/particulate respirator or an air supplied mask meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from the following material(s) should be suitable for intermittent contact, however, due to variations in glove construction and local conditions, a final assessment should be made by the user: nitrile-butadiene rubber, butyl rubber, polyethylene, neoprene, PVC. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:** Liquid  
**Colour:** Amber to Dark Brown  
**Odour:** Slight Amine / Fluorocarbon  
**Solubility:** Partially soluble in water.

Product Name: SILENT SEAL B - COMPONENT  
Substance No: 000000052115

Issued: 15/02/2018  
Version: 4

# Safety Data Sheet



|   |  |
|---|--|
| <b>Specific Gravity:</b>                | 1.2 @ 25°C approx.   |
| <b>Relative Vapour Density (air=1):</b> | Not available  |
| <b>Vapour Pressure (20 °C):</b>         | >345 kPa (contents under pressure); <1 mmHg at 40°C (liquid phase) |
| <b>Flash Point (°C):</b>                | >200 (estimated)   |
| <b>Flammability Limits (%):</b>         | Not available  |
| <b>Autoignition Temperature (°C):</b>   | Not available  |
| <b>% Volatile by Weight:</b>            | Not available  |
| <b>Boiling Point/Range (°C):</b>        | -26 (propellant); >93 (liquid phase)                               |
| <b>Decomposition Point (°C):</b>        | Not available  |
| <b>pH:</b>                              | Not applicable   |
| <b>Viscosity:</b>                       | Not available  |
| <b>Evaporation Rate:</b>                | Not available  |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Reactivity:</b>                         | No information available.  |
| <b>Chemical stability:</b>                 | Stable under normal conditions of use.   |
| <b>Possibility of hazardous reactions:</b> | Heating can cause expansion or decomposition of the material, which can lead to the containers exploding.  |
| <b>Conditions to avoid:</b>                | Avoid exposure to heat, sources of ignition, and open flame. Avoid temperatures below 16°C. Avoid temperatures above 32°C. Exposure to elevated temperatures can cause product to decompose. |
| <b>Incompatible materials:</b>             | Incompatible with alcohols, amines, ammonia, strong bases, metal compounds and oxidising agents.   |
| <b>Hazardous decomposition products:</b>   | Hydrogen cyanide. Hydrogen fluoride. Oxides of carbon. Oxides of nitrogen. Aldehydes.  |

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

|                      |   |
|----------------------|---|
| <b>Ingestion:</b>    | Swallowing can result in nausea, vomiting, diarrhoea, and abdominal pain.   |
| <b>Eye contact:</b>  | An eye irritant. May cause temporary corneal injury.  |
| <b>Skin contact:</b> | Contact with skin will result in irritation.  |
| <b>Inhalation:</b>   | Material is irritant to the mucous membranes of the respiratory tract (airways). May cause coughing, sore throat, headache, dizziness, drowsiness and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. |

**Acute toxicity:** No LD50 data available for the product.

|   |                 |
|---|-----------------|
| <b>Skin corrosion/irritation:</b>         | Irritant.       |
| <b>Serious eye damage/irritation:</b>     | Irritant.       |
| <b>Respiratory or skin sensitisation:</b> | Not classified. |

Product Name: SILENT SEAL B - COMPONENT  
Substance No: 000000052115

Issued: 15/02/2018  
Version: 4

# Safety Data Sheet



**Chronic effects:** No information available for the product.

**Mutagenicity:** Not classified.  
**Carcinogenicity:** Not classified.  
**Reproductive toxicity:** Not classified.  
**Specific Target Organ Toxicity (STOT) - single exposure:** No information available.  
**Specific Target Organ Toxicity (STOT) - repeated exposure:** No information available.  
**Aspiration hazard:** No information available.  
A cholinesterase inhibitor.

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity** Avoid contaminating waterways.  
**Persistence/degradability:** This product is readily biodegradable.  
**Bioaccumulative potential:** Not expected to bioaccumulate.  
**Mobility in soil:** No information available.

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods:

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations. Do not incinerate.

Wear personal protective equipment and in a well-ventilated area when handling.

1. Empty cylinders by dispensing the product into a waste container like a cardboard box or plastic bag. Depressurise the used cylinders using the dispensing unit with a new nozzle attached. Spray the product until one of the components/cylinders no longer sprays chemical.

2. Remove the nozzle and then continue to depressurise by dispensing the remaining product(s) into a waste container (a box lined with a plastic bag) that has adequate industrial liquid absorbing medium in the bottom. Dispense the residual chemicals until the pressure is down to a minimum or there are just large bubbles in the hose.

3. Close the cylinder valves completely, and then operate the dispensing unit again to empty and depressurise the hoses. Use a 9/16" wrench and remove the hoses from the cylinders. Use caution in case there is some residual chemical and/or pressure in the hoses.

4. Invert the cylinder and point away from face. Slowly open the cylinder over the waste container to catch any residual spray.

5. Return the cylinder to an upright position. Shake the container; there should not be any sloshing of liquid. Make sure to leave valves OPEN – do not close. DO NOT PUNCTURE.

Treat as hazardous material if product is still present in the cylinder after dispensing.

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



Product Name: SILENT SEAL B - COMPONENT  
Substance No: 000000052115

Issued: 15/02/2018  
Version: 4

# Safety Data Sheet



**UN No:** 3500  
**Transport Hazard Class:** 2.2 Non-Flammable Non-Toxic Gas  
**Proper Shipping Name or Technical Name:** CHEMICAL UNDER PRESSURE, N.O.S. (FLUORINATED HYDROCARBON, NITROGEN)  
**Hazchem or Emergency Action Code:** 2ZE

## Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

**UN No:** 3500  
**Transport Hazard Class:** 2.2 Non-Flammable Non-Toxic Gas  
**Proper Shipping Name or Technical Name:** CHEMICAL UNDER PRESSURE, N.O.S. (FLUORINATED HYDROCARBON, NITROGEN)  
**IMDG EMS Fire:** F-C  
**IMDG EMS Spill:** S-V

## Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

**UN No:** 3500  
**Transport Hazard Class:** 2.2 Non-Flammable Non-Toxic Gas  
**Proper Shipping Name or Technical Name:** CHEMICAL UNDER PRESSURE, N.O.S. (FLUORINATED HYDROCARBON, NITROGEN)

## 15. REGULATORY INFORMATION

### Classification:

This material is hazardous according to Safe Work Australia; HAZARDOUS CHEMICAL.

### Classification of the chemical:

Gases under pressure - Compressed Gas  
Acute Oral Toxicity - Category 4  
Skin Irritation - Category 2  
Eye Irritation - Category 2A

### Hazard Statement(s):

H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

**Poisons Schedule (SUSMP):** None allocated.

## 16. OTHER INFORMATION

Supplier Safety Data Sheet; 12/ 2017.

This safety data sheet has been prepared by Ixom Operations Pty Ltd (Toxicology & SDS Services).

# Safety Data Sheet



## Reason(s) for Issue:

Revised Primary SDS  
Change in company details  
Change in Hazardous Chemical Classification  
Updated Formulation  
Change in First Aid Measures  
Change in Exposure Controls  
Change in Physical Properties  
Update in Toxicological Information  
Update in Ecological Information  
Change in Disposal requirements  
Change to Transport Information

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since The Supplier cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Supplier representative or The Supplier at the contact details on page 1.

The Supplier's responsibility for the material as shipped is subject to the terms and conditions of sale, a copy of which is available upon request.